



NIEUWKOOP

LEAFLET



EC5501

EC+TEMP TRANSMITTER



TO MEASURE  TO KNOW

EC5501

EC+TEMP TRANSMITTER



NIEUWKOOP



Toroidal loop powered transmitters

- ST 3254.1** : scale 0/10 mS range
- ST 3254.2** : scale 0/100 mS range
- ST 3254.3** : scale 0/1000 mS range
- ST 3214.4** : scale 0/20 mS range
- ST 3214.5** : scale 0/200 mS range
- ST 3214.6** : scale 0/2000 mS range

On request it is available a model with range 0/300 mS
 This E. Conductivity probe consists of a loop powered transmitter and an electrodeless conductivity sensor in a single package. Temperature compensation is accomplished with a built-in sensor.

Applications include water treatment, cooling tower and water monitoring.

Six models are available for specific measuring range.



Principle of operation

When the electrodeless conductivity sensor is immersed in the sample to be measured, a conductive loop is created through the two, toroidally wound coils. An alternating current is applied to one of the coils which induces a current in the conductive loop.

The second coil is used to measure the conductivity which is proportional to the induced current in the solution.

The advantages of the electrodeless method are more apparent in measurement applications in which electrodes contamination and polarization of a conventional conductivity system can lead to erroneous readings.

Each probe contains:

- two measuring toroidal coils
- temperature sensor
- 4-20 mA current loop amplifier

Technical Specifications

Measuring method: toroidal
Power supply: 11/30 Vdc
Temperature sensor: built-in
Load: 600 ohm max. at 24 Vdc
Max. temperature: 50 °C part in contact with liquid
Temperature coefficient: 2.2 %/°C (2.0 for ST 3214.X)
Temperature reference: 25 °C (20 °C for ST 3214. X)
Max. pressure: 10 bar at 25 °C
Length: 207 mm
Thread: 1 1/2" MNPT (both sides)
Body: PVC-C
Cable length: 3 m
Installation: in-line or submersible



TO MEASURE  TO KNOW

Nieuwkoop BV

Aalsmeerderweg 249-S
1432 CM AALSMEER

0297 325836

info@nieuwkoopbv.nl
www.meten.nl



NIEUWKOOP