



NIEUWKOOP

LEAFLET



EC3005 CONTROLLER



TO MEASURE  TO KNOW



Controllers with 1 set-point

LCD Display

Automatic temperature compensation

Set point values display

HI/LO selectable limits

Adjustable relay time delay

4/20 mA output

Detachable terminal block

PH 3645

pH controller

Scale: 0/14.00 pH

ATC: NTC 10K



MV 3645

O.R.P. controller

Scale: 0/1000 mV



C3645

E. Conductivity controller

Scale: 0/1999 μ S

Option 091.1321: scale 0/199,9 μ S

Option 091.1322: scale 0/19,99 mS

Input: 2-electrode E.C. cell 4-electrode E.C. cell

ATC: NTC 10K

Temperature coefficient: 2 %/°C



TR3645

Temperature controller

Scale: -20/+120 °C

Input: RTD Pt100 (3 wire)



Technical specifications

Display: LCD

Zero Adjustment: \pm 15%

Slope Adjustment: \pm 20%

Automatic Temperature Compensation: NTC 10K (Pt100 for C3655)

Output: 4.20 mA dc 300 ohm max

Relay contacts: SPDT 220 V 5 A resistive load

Hysteresis: \pm 0.25%

Switching Time: < 0.5 s

Relay Time Delay: adjustable 0/40 s

Operating Temperature: 0/50 °C

Operating Humidity: 0/95% R.H. non-condensing

Power supply: 110/220 V \pm 10% 50/60 Hz 2 VA

Isolation: 4 kV (Iec 348)

Weight: 265 g

Dimensions: 105 x 95 x 90 mm (6 DIN Rail modules)

Mounting: DIN Rail (35 x 7.5 mm Rail)

Option 091.402: 24 Vac power supply



3000 Series DIN RAIL

- High accuracy**
- High reliability**
- Modular design**
- Low installation costs**
- Compact size**

General information

This series of analyzers and transmitters has been designed for the measurement and control of:

- pH
- O.R.P.
- Conductivity
- Electrodeless Conductivity
- Residual Chlorine
- Temperature

For OEM applications in industrial process, with continuous readings on LCD display.

These instruments provide accurate, low cost measuring and control for industrial process, water treatment and wastewater applications.

The Series is made of 3 different models, which allow Customers to select the most suitable solution according to their application and installation.

Models **3645** and **3655** feature one relay and a 4...20 mA output, not isolated.

Models **3647** are same as the models above, but with 2 relays.

Models **3630**, thanks to a "current-loop" 4...20 mA output, are the ideal solution for those installations where controlling is done via PLC or other remote supervision and control devices, without losing the possibility to calibrate near the sensor.

Accessories for installation



BC 9408

Water-tight enclosure for 1 unit

Protection: IP65 (NEMA 4X)

Dimensions: 205 x 220 x 140 mm



BC 9412

Water-tight enclosure for 2 units

Protection: IP65 (NEMA 4X)

Dimensions: 275 x 220 x 140 mm

BC 9491

Wall mounting brackets for BC9408 and BC 9412

BC 95106

Frame for panel mounting of DIN Rail instrument (6 modules).



TO MEASURE  TO KNOW

Nieuwkoop BV

Aalsmeerderweg 249 -S

1432 CM AALSMEER

0297 325836

info@nieuwkoopbv.nl

www.meten.nl



NIEUWKOOP